
HYD-104L-CK5-40W 3000K

Panel light

DESCRIPTION

The large panel light adopts high-transparency diffuser plates to ensure uniform illumination and soft light on the light-emitting surface, reducing glare. It is available in various installation methods such as recessed, surface-mounted, and suspended, making it suitable for all kinds of lighting spaces with excellent adaptability. It features an integrated aluminum heat dissipation structure to keep the LED junction temperature within the optimal working range, guaranteeing an extremely long service life (over 50,000 hours). The 104L-CK5 large panel light series, with its superior quality and ultimate adaptability, creates a healthy, comfortable, and efficient lighting environment for commercial and public spaces, making it a reliable lighting partner.





ELECTRICAL FEATURES

Power	40 W
Input Voltage	AC220 - 240V
Line Frequency	50/60 Hz
Powered By	HYUNDAI
Dimmable	No
Control interface	No


PRODUCT SPECIFICATION


Luminiaire luminous flux	4200 lm
Efficiency	105 lm/w
CCT	3000 k
CRI	⩾80
Beam Angle	85°
Life span	50,000 h
Light source	LM80 Module - SMD

TECHNICAL FEATURES

Materials	Die-cast aluminum
Surface Material	Lampshade-White (SPCC)
Body Color	Grey Housing
Adjustability	Not Adjustable
IP Class	IP50
Installation way	Recessed Suspendant
Dimension	W595 x L595 x H25
Cut Dimension	N/A

IES FEATURES





APPROVAL AND APPLICATION

Standard	CB,CE,ROHS,SAA
Working temperature	-10 °C ~ + 40 °C

PACKAGE SIZE

PCS/CTN	-
Carton Size	-

APPLICATIONS

Healthcare, Schools, Supermarkets, Hospitals & Clinics, Government institutions, Other indoor public places, Hotel, Dining room

