
HYD-415-50W 3000K

Floodlight

DESCRIPTION

The HYD-415 floodlight features a structure made of precision aluminum and is equipped with high-transparency tempered glass mirror, offering outstanding resistance to vibration, impact and corrosion. It has a professional IP65 protection rating, enabling it to handle severe conditions such as heavy rain, sandstorms and extreme cold with ease. It is highly suitable for both indoor and outdoor use, providing long-term and stable lighting assurance. It adopts high-quality LED light sources, which maintain stable performance over a long period, significantly expanding the illumination range and improving energy efficiency. It is applicable to various scenarios and creates clear, safe and efficient spatial value with high-quality light.





ELECTRICAL FEATURES

Power	50 W
Input Voltage	AC100 - 277V
Powered By	HYUNDAI
Dimmable	No
Control interface	No


PRODUCT SPECIFICATION


Luminiaire luminous flux	6150 lm
Efficiency	123 lm/w
CCT	3000 k
CRI	⩾80
Beam Angle	90°
Life span	50,000 h
Light source	LM80 Module - SMD

TECHNICAL FEATURES

Materials	Die-cast aluminum
Surface Material	Lampshade-transparent (Glass)
Body Color	Grey Housing
Adjustability	Tilted
IP Class	IP65
Installation way	Surface
Dimension	W305 x L215 x H65
Cut Dimension	N/A

IES FEATURES





APPROVAL AND APPLICATION

Standard	CB,CE,ROHS
Working temperature	-10 °C ~ + 50 °C

PACKAGE SIZE

PCS/CTN	-
Carton Size	-

APPLICATIONS

factory, Warehouses, outdoor, Parking lots, Building lighting, loading areas, outdoor light applications

