
HYD-518-150W 3000K

Street Light

DESCRIPTION

As an innovative solution designed for modern urban road lighting, this series of LED street lamps integrates numerous advantages such as high efficiency and energy conservation, excellent environmental adaptability, and an extremely long service life, meeting the diverse lighting needs of various scenarios. The product is made of die-cast aluminum alloy, with a protection level conforming to IP65 standards. It adopts high-quality LED chips, with a service life of up to 50,000 hours, effectively reducing the cost of later maintenance. It features a modern and simple design style, which can harmoniously blend with different urban landscapes.





ELECTRICAL FEATURES

Power	**150 W**
Input Voltage	**AC165 - 265V**
Line Frequency	**50/60 Hz**
Power Factor (Fraction)	**0.9**
Powered By	**HYUNDAI**
Dimmable	**No**
Control interface	**No**

PRODUCT SPECIFICATION

Luminiaire luminous flux	**23400 lm**
Efficiency	**156 lm/w**
CCT	**3000 k**
CRI	**⩾80**
Beam Angle	**105°**
Life span	**50,000 h**
Light source	**LM80 Module - SMD**

TECHNICAL FEATURES

Materials	**Die-cast aluminum**
Surface Material	**Lampshade-transparent (PC)**
Body Color	**Grey Housing**
Adjustability	**Not Adjustable**
IP Class	**IP65**
Mech.impact protection code	**IK06**
Installation way	**Mounted on pole**
Dimension	**W241 x L663 x H83**
Cut Dimension	**N/A**

APPLICATIONS

factory, Warehouses, outdoor, Roads, Highways



APPROVAL AND APPLICATION

Standard	**CE**
Working temperature	**-30 °C ~ + 50 °C**

PACKAGE SIZE

PCS/CTN	**-**
Carton Size	**-**