
HYD-518-150W 6000K

Street Light

DESCRIPTION

As an innovative solution designed for modern urban road lighting, this series of LED street lamps integrates numerous advantages such as high efficiency and energy conservation, excellent environmental adaptability, and an extremely long service life, meeting the diverse lighting needs of various scenarios. The product is made of die-cast aluminum alloy, with a protection level conforming to IP65 standards. It adopts high-quality LED chips, with a service life of up to 50,000 hours, effectively reducing the cost of later maintenance. It features a modern and simple design style, which can harmoniously blend with different urban landscapes.





ELECTRICAL FEATURES

Power	150 W
Input Voltage	AC165 - 265V
Line Frequency	50/60 Hz
Power Factor (Fraction)	0.9
Powered By	HYUNDAI
Dimmable	No
Control interface	No

PRODUCT SPECIFICATION

Luminiaire luminous flux	23400 lm
Efficiency	156 lm/w
CCT	6000 k
CRI	⩾80
Beam Angle	105°
Life span	50,000 h
Light source	LM80 Module - SMD

TECHNICAL FEATURES

Materials	Die-cast aluminum
Surface Material	Lampshade-transparent (PC)
Body Color	Grey Housing
Adjustability	Not Adjustable
IP Class	IP65
Mech.impact protection code	IK06
Installation way	Mounted on pole
Dimension	W241 x L663 x H83
Cut Dimension	N/A

APPLICATIONS

factory, Warehouses, outdoor, Roads, Highways



APPROVAL AND APPLICATION

Standard	CE
Working temperature	-30 °C ~ + 50 °C

PACKAGE SIZE

PCS/CTN	-
Carton Size	-