

HYD-O1-12W 6000K

Wall light

DESCRIPTION

This luminaire is a high-performance LED wall light, meticulously engineered to meet the dual demands of high-intensity illumination and visual aesthetics for both indoor and outdoor environments. By integrating high-efficiency LED light sources with professional optical design, it delivers exceptional center beam intensity while achieving wide and uniform light distribution. The housing, constructed from premium materials and rated IP65, stands resilient against wind and rain, ensuring reliable, long-lasting performance for flood and safety lighting applications such as building facades, corridors, entrances, and parking areas.





ELECTRICAL FEATURES

Power	12 W
Input Voltage	AC180 - 260V
Line Frequency	50/60 Hz
Power Factor (Fraction)	0.9
Powered By	HYUNDAI
Dimmable	No
Control interface	No


PRODUCT SPECIFICATION


Luminiaire luminous flux	1416 lm
Efficiency	118 lm/w
CCT	6000 k
CRI	⩾80
Beam Angle	120°
Life span	20,000 h
Light source	LM80 Module - SMD

TECHNICAL FEATURES

Materials	PC
Surface Material	Diffuser cover-White (PC)
Body Color	White
Adjustability	Not Adjustable
IP Class	IP65
Mech.impact protection code	IK02
Installation way	Wall mounted
Dimension	D165 x H53
Cut Dimension	N/A

IES FEATURES






APPROVAL AND APPLICATION

Standard	CB,CE
Working temperature	-10 °C ~ + 45 °C

APPLICATIONS

factory, Warehouses, Supermarkets, Parking lots, Villas, Hotel, Outdoor porch, Courtyard wall



PACKAGE SIZE

PCS/CTN	-
Carton Size	-