


HYD-O2-20W 6000K

Wall light

DESCRIPTION

This luminaire is a high-performance LED wall light, meticulously engineered to meet the dual demands of high-intensity illumination and visual aesthetics for both indoor and outdoor environments. By integrating high-efficiency LED light sources with professional optical design, it delivers exceptional center beam intensity while achieving wide and uniform light distribution. The housing, constructed from premium materials and rated IP65, stands resilient against wind and rain, ensuring reliable, long-lasting performance for flood and safety lighting applications such as building facades, corridors, entrances, and parking areas.



ELECTRICAL FEATURES

Power	20 W
Line Frequency	50/60 Hz
Powered By	HYUNDAI
Dimmable	No
Control interface	No

TECHNICAL FEATURES

Materials	PC
Surface Material	Lampshade-White (PC)
Body Color	White
Adjustability	Not Adjustable
IP Class	IP65
Installation way	Wall mounted
Dimension	W144 x L270 x H69
Cut Dimension	N/A

APPROVAL AND APPLICATION

Standard	CB,CE,ROHS,SAA
Working temperature	-10 °C ~ + 45 °C


PACKAGE SIZE

PCS/CTN	-
Carton Size	-

PRODUCT SPECIFICATION

Luminaire luminous flux	2320 lm
Efficiency	116 lm/w
CCT	6000 k
CRI	≥80
Beam Angle	120°
Life span	20,000 h
Light source	LM80 Module - SMD

IES FEATURES



APPLICATIONS

factory, Warehouses, Supermarkets, Parking lots, Villas, Hotel, Outdoor porch, Courtyard wall

