


HYD-W20B-11W 4000K

Wall light

DESCRIPTION

Wall lamps provide focused illumination, enabling precise local lighting. They can also function as supplementary light sources to the primary lighting, effectively minimizing dark zones and creating a uniform, soft, and glare-free lighting environment. Furthermore, their gentle light output makes them suitable for use as night lights or pathway indicators. Wall lamps exemplify the advantage of Versatility, serving not only as practical lighting fixtures but also as aesthetic decorative elements. They enhance spatial ambiance while fulfilling functional needs, thereby improving both living quality and perceived safety.



ELECTRICAL FEATURES

Power	11 W
Input Voltage	AC220 - 240V
Line Frequency	50/60 Hz
Power Factor (Fraction)	0.5
Powered By	HYUNDAI
Dimmable	No
Control interface	No

TECHNICAL FEATURES

Materials	Aluminum
Surface Material	Diffuser cover-White (PC)
Body Color	BLACK
Adjustability	Not Adjustable
IP Class	IP65
Installation way	Wall mounted
Dimension	D220 x H71
Cut Dimension	N/A

APPROVAL AND APPLICATION

Standard	CE
Working temperature	-10 °C ~ + 45 °C


PACKAGE SIZE

PCS/CTN	-
Carton Size	-

PRODUCT SPECIFICATION

Luminaire luminous flux	803 lm
Efficiency	73 lm/w
CCT	4000 k
CRI	≥80
Beam Angle	110°
Life span	50,000 h
Light source	LM80 Module - SMD

IES FEATURES



APPLICATIONS

porchs, Villas, Stairs, Hotel, Bedroom, Porch, Dining room, Outdoor porch, Courtyard wall

