
HYD-614-7W 5CCT BK

Track Light

DESCRIPTION

The angle and direction of the light head of the track light can be flexibly adjusted to achieve precise lighting and meet the needs of various scenarios. This product is compatible with standard tracks and has a plug-and-play feature, eliminating the need for wiring or tools. The installation process is time-saving and labor-saving, and even without professional experience, it can be easily completed. The track light adopts high-quality heat dissipation materials, which can effectively reduce the working temperature and thus extend the service life. The efficient LED light source has the advantage of energy saving and power saving, which can significantly reduce the cost of use.





ELECTRICAL FEATURES

Power	10 W
Input Voltage	AC220 - 240V
Line Frequency	50/60 Hz
Power Factor (Fraction)	0.5
Powered By	HYUNDAI
Dimmable	No
Control interface	No


PRODUCT SPECIFICATION


Luminiaire luminous flux	1060 lm
Efficiency	106 lm/w
CCT	Switchable (2700, 3000, 4000, 5000, 6500)
CRI	⩾80
Beam Angle	35°
Life span	20,000 h
Light source	LM80 Module - SMD

TECHNICAL FEATURES

Materials	Aluminum
Surface Material	Lens-transparent (PC)
Body Color	BLACK
Adjustability	Tilted & Rotated
IP Class	IP20
Mech.impact protection code	IK08
Installation way	On rail
Dimension	D54 x H170
Cut Dimension	N/A

IES FEATURES





APPROVAL AND APPLICATION

Standard	-
Working temperature	-20 °C ~ + 40 °C

APPLICATIONS

Healthcare, Offices, Schools, Supermarkets, Commercial applications, Hotel



PACKAGE SIZE

PCS/CTN	20
Carton Size	L33 x W29 x H21