
HYD-GU10L-7W 3000K

GU10

DESCRIPTION

The GU10 product features precise beam angles and outstanding energy-saving performance. It is designed with a standard GU10 interface, allowing for plug-and-play functionality without the need to modify existing wiring, making installation and replacement extremely convenient. Additionally, it supports a wide operating temperature range from −20° C to +40° C, ensuring stable and reliable operation.





ELECTRICAL FEATURES

Power	7 W
Input Voltage	AC220 - 240V
Line Frequency	50/60 Hz
Power Factor (Fraction)	0.5
Powered By	HYUNDAI
Dimmable	No
Control interface	No


PRODUCT SPECIFICATION


Luminiaire luminous flux	777 lm
Efficiency	111 lm/w
CCT	3000 k
CRI	⩾80
Beam Angle	25°
Life span	20,000 h
Light source	LM80 Module - SMD

TECHNICAL FEATURES

Materials	PA
Surface Material	Lens-semi transparent (PC)
Body Color	White
Adjustability	Not Adjustable
IP Class	IP20
Mech.impact protection code	IK06
Installation way	Base: GU10
Dimension	D50 x H56
Cut Dimension	N/A

IES FEATURES





APPROVAL AND APPLICATION

Standard	CE
Working temperature	-20 °C ~ + 40 °C

APPLICATIONS

Healthcare, Offices, Showrooms, Shopping malls, Villas, Museums, Hotel



PACKAGE SIZE

PCS/CTN	-
Carton Size	-