
HYD-T54 1281

Tri-Proof

DESCRIPTION

This triple proof luminaire features a waterproof, dustproof, and corrosion resistant three layer protection architecture, together with excellent vibration and impact resistance. Its high grade protective structure has been rigorously tested and optimised to deliver lasting, reliable protection for internal components. The luminaire is also compatible with mainstream T8 tubes on the market, allowing easy replacement, and when paired with a high efficiency LED light source, its overall performance is significantly enhanced.





ELECTRICAL FEATURES

Powered By	-
Dimmable	No
Control interface	No

PRODUCT SPECIFICATION

Luminiaire luminous flux	-
Efficiency	-
Beam Angle	-
Life span	20,000 h
Light source	-

TECHNICAL FEATURES

Materials	PC
Surface Material	Diffuser cover-transparent (PC)
Body Color	White
Adjustability	Not Adjustable
IP Class	IP65
Mech.impact protection code	IK06
Installation way	Surface
Dimension	W94 x L1281 x H69
Cut Dimension	N/A

APPLICATIONS

factory, Warehouses, outdoor, Parking lots, loading areas, Gymnasium



APPROVAL AND APPLICATION

Standard	CE
Working temperature	-20 °C ~ + 40 °C

PACKAGE SIZE

PCS/CTN	1
Carton Size	-