



HYD-104L5-40W 6000K UGR 22

Panel light

DESCRIPTION

The large panel light adopts high-transparency diffuser plates to ensure uniform illumination and soft light on the light-emitting surface, reducing glare. It is available in various installation methods such as recessed, surface-mounted, and suspended, making it suitable for all kinds of lighting spaces with excellent adaptability. The 104-L5 large panel light series, with its superior quality and ultimate adaptability, creates a healthy, comfortable, and efficient lighting environment for commercial and public spaces, making it a reliable lighting partner.



ELECTRICAL FEATURES

Power	40 W
Powered By	HYUNDAI
Dimmable	No
Control interface	No

TECHNICAL FEATURES

Materials	Iron
Surface Material	Diffuser-White (PS)
Body Color	White
Adjustability	Not Adjustable
IP Class	IP20
Installation way	Recessed
Dimension	W595 x L595 x H25
Cut Dimension	N/A

APPROVAL AND APPLICATION

Working temperature	-10 °C ~ + 40 °C
---------------------	------------------


PACKAGE SIZE

PCS/CTN	1
Carton Size	-

PRODUCT SPECIFICATION

Luminaire luminous flux	4640 lm
Efficiency	116 lm/w
CCT	6000 k
CRI	≥80
Beam Angle	115°
Life span	50,000 h
Light source	LM80 Module - SMD

IES FEATURES



APPLICATIONS

Healthcare, Offices, Schools, Supermarkets, Office, Meeting room

