
HYD-122S-24W 3000K

Panel light

DESCRIPTION

The surface–mounted panel light adopts high–quality LED chips, achieving higher luminous efficacy. It is also equipped with a well–known brand driver to ensure a product lifespan of over 30,000 hours. This luminaire is specifically designed for architectural spaces without suspended ceilings or pre–buried conduits, and can perfectly adapt to various venues.
The HYD – 122S surface–mounted panel light, with its outstanding comprehensive performance, is dedicated to creating a bright, comfortable, healthy, and productivity–enhancing lighting environment for users. It is the ideal lighting choice for modern spaces that pursue quality and efficiency.



ELECTRICAL FEATURES

Power	24 W
Powered By	HYUNDAI
Dimmable	No
Control interface	No


PRODUCT SPECIFICATION


Luminiaire luminous flux	1536 lm
Efficiency	64 lm/w
CCT	3000 k
CRI	⩾80
Beam Angle	115°
Life span	50,000 h
Light source	LM80 Module - SMD

TECHNICAL FEATURES

Materials	Aluminum
Surface Material	Diffuser-White (PC)
Body Color	White
Adjustability	Not Adjustable
IP Class	IP20
Installation way	Ceiling
Dimension	W175 x L175 x H30
Cut Dimension	N/A

IES FEATURES





APPROVAL AND APPLICATION

Standard	CB,CE
Working temperature	-10 °C ~ + 40 °C

APPLICATIONS

Healthcare, Offices, factory, Schools, Supermarkets, Restaurants

PACKAGE SIZE

PCS/CTN	1
Carton Size	-

