


## HYD-W88-8W 4000K Antique Bronze

Wall light

### DESCRIPTION

Wall lamps provide focused illumination, enabling precise local lighting. They can also function as supplementary light sources to the primary lighting, effectively minimizing dark zones and creating a uniform, soft, and glare-free lighting environment. Furthermore, their gentle light output makes them suitable for use as night lights or pathway indicators. Wall lamps exemplify the advantage of Versatility, serving not only as practical lighting fixtures but also as aesthetic decorative elements. They enhance spatial ambiance while fulfilling functional needs, thereby improving both living quality and perceived safety.



### ELECTRICAL FEATURES

|                         |              |
|-------------------------|--------------|
| Power                   | 8 W          |
| Input Voltage           | AC220 - 240V |
| Line Frequency          | 50/60 Hz     |
| Power Factor (Fraction) | 0.5          |
| Powered By              | HYUNDAI      |
| Dimmable                | No           |
| Control interface       | No           |

### TECHNICAL FEATURES

|                             |                          |
|-----------------------------|--------------------------|
| Materials                   | Aluminum                 |
| Surface Material            | Lens-transparent (Glass) |
| Body Color                  | Antique Bronze           |
| Adjustability               | Not Adjustable           |
| IP Class                    | IP65                     |
| Mech.impact protection code | IK04                     |
| Installation way            | Wall mounted             |
| Dimension                   | W95 x L108 x H82         |
| Cut Dimension               | N/A                      |

### APPROVAL AND APPLICATION

|                     |                  |
|---------------------|------------------|
| Working temperature | -20 °C ~ + 40 °C |
|---------------------|------------------|

### PACKAGE SIZE

|             |   |
|-------------|---|
| PCS/CTN     | 1 |
| Carton Size | - |

### PRODUCT SPECIFICATION

|                         |                   |
|-------------------------|-------------------|
| Luminaire luminous flux | 560 lm            |
| Efficiency              | 70 lm/w           |
| CCT                     | 4000 k            |
| CRI                     | ≥90               |
| Beam Angle              | 85°               |
| Life span               | 30,000 h          |
| Light source            | LM80 Module - COB |

### APPLICATIONS

Villas, Museums, Hotel, Bedroom, Porch, Dining room, Living room

