

## HYD-C808-8W 2700K Antique Bronze

### Ceiling Light

#### DESCRIPTION

The HYD-C808 ceiling light is constructed from high-quality aluminum alloy and has undergone a precise oxidation treatment process, ensuring a robust structure and excellent load-bearing capacity. The fixture maintains dimensional stability and resists deformation even under prolonged use. The lampshade is fabricated from imported-grade polycarbonate (PC) material, offering a light transmittance exceeding 90%. This results in soft and uniform illumination, effectively minimizing glare and providing enhanced visual comfort for household occupants. Furthermore, the lampshade surface features a specialized coating that provides dust-resistant and anti-yellowing properties, preserving its aesthetic appearance and ensuring long-term brightness and luster.

#### ELECTRICAL FEATURES

|                         |              |
|-------------------------|--------------|
| Power                   | 8 W          |
| Input Voltage           | AC220 - 240V |
| Line Frequency          | 50/60 Hz     |
| Power Factor (Fraction) | 0.5          |
| Powered By              | HYUNDAI      |
| Dimmable                | No           |
| Control interface       | No           |

#### TECHNICAL FEATURES


|                             |                          |
|-----------------------------|--------------------------|
| Materials                   | Aluminum                 |
| Surface Material            | Lens-transparent (Glass) |
| Body Color                  | Antique Bronze           |
| Adjustability               | Not Adjustable           |
| IP Class                    | IP20                     |
| Mech.impact protection code | IK04                     |
| Installation way            | Surface                  |
| Dimension                   | D108 x H93               |
| Cut Dimension               | N/A                      |

#### APPROVAL AND APPLICATION

|                     |                  |
|---------------------|------------------|
| Working temperature | -20 °C ~ + 40 °C |
|---------------------|------------------|

#### PACKAGE SIZE

|             |   |
|-------------|---|
| PCS/CTN     | 1 |
| Carton Size | - |



#### PRODUCT SPECIFICATION

|                         |                   |
|-------------------------|-------------------|
| Luminaire luminous flux | 560 lm            |
| Efficiency              | 70 lm/w           |
| CCT                     | 2700 k            |
| CRI                     | ≥90               |
| Beam Angle              | 85°               |
| Life span               | 30,000 h          |
| Light source            | LM80 Module - COB |

#### APPLICATIONS

Hospitals & Clinics, Hotel, Bedroom, Dining room, Living room, Office, Meeting room

