

HYD-C808-8W 4000K Chrome

Ceiling Light

DESCRIPTION

The HYD-C808 ceiling light is constructed from high-quality aluminum alloy and has undergone a precise oxidation treatment process, ensuring a robust structure and excellent load-bearing capacity. The fixture maintains dimensional stability and resists deformation even under prolonged use. The lampshade is fabricated from imported-grade polycarbonate (PC) material, offering a light transmittance exceeding 90%. This results in soft and uniform illumination, effectively minimizing glare and providing enhanced visual comfort for household occupants. Furthermore, the lampshade surface features a specialized coating that provides dust-resistant and anti-yellowing properties, preserving its aesthetic appearance and ensuring long-term brightness and luster.

ELECTRICAL FEATURES

Power	8 W
Input Voltage	AC220 - 240V
Line Frequency	50/60 Hz
Power Factor (Fraction)	0.5
Powered By	HYUNDAI
Dimmable	No
Control interface	No

TECHNICAL FEATURES


Materials	Aluminum
Surface Material	Lens-transparent (Glass)
Body Color	Chrome
Adjustability	Not Adjustable
IP Class	IP20
Mech.impact protection code	IK04
Installation way	Surface
Dimension	D108 x H93
Cut Dimension	N/A

APPROVAL AND APPLICATION

Working temperature	-20 °C ~ + 40 °C
---------------------	------------------

PACKAGE SIZE

PCS/CTN	1
Carton Size	-



PRODUCT SPECIFICATION

Luminaire luminous flux	560 lm
Efficiency	70 lm/w
CCT	4000 k
CRI	≥90
Beam Angle	85°
Life span	30,000 h
Light source	LM80 Module - COB

APPLICATIONS

Hospitals & Clinics, Hotel, Bedroom, Dining room, Living room, Office, Meeting room

