



HYD-425A-240W 5K Ra80

Floodlight

Description

The HYD-425A floodlight features a structure made of precision aluminum and is equipped with high-transparency tempered glass mirror, offering outstanding resistance to vibration, impact and corrosion. It has a professional IP66 protection rating, enabling it to handle severe conditions such as heavy rain, sandstorms and extreme cold with ease. It is highly suitable for both indoor and outdoor use, providing long-term and stable lighting assurance. It adopts high-quality LED light sources, which maintain stable performance over a long period, significantly expanding the illumination range and improving energy efficiency. It is applicable to various scenarios and creates clear, safe and efficient spatial value with high-quality light.

Product Specification

Power	240 W
Luminaire luminous flux	35760 lm
Efficiency	149 lm/w
CCT	5000 k
CRI	≥80
Beam Angle	110°
Working temperature	-30 to + 50 °C
Life span	50,000 h
IP	66
IK	08
Dimension	W434 x L504 x H63

Technical Features

Materials	Housing-BLACK-Aluminum
Surface Material	Lampshade-Translucent color-Glass
Installation way	Surface
Adjustability	Tilted

Applications

factory, Warehouses, outdoor, Parking lots, Building lighting, Exterior walls

Electrical Features

Light source	LM80 SMD Module - SMD
Powered By	HYUNDAI

Scene Application



IES Features

