



HYD-508-250W 6K Floodlight

Description

The HYD-508 floodlight features a structure made of precision aluminum, offering outstanding resistance to vibration, impact and corrosion. It has a professional IP65 protection rating, enabling it to handle severe conditions such as heavy rain, sandstorms and extreme cold with ease. It is highly suitable for both indoor and outdoor use, providing long-term and stable lighting assurance. It adopts high-quality LED light sources, which maintain stable performance over a long period, significantly expanding the illumination range and improving energy efficiency. It is applicable to various scenarios and creates clear, safe and efficient spatial value with high-quality light.

Product Specification

Power	250 W
Luminaire luminous flux	32750 lm
Efficiency	131 lm/w
CCT	6000 k
CRI	≥80
Beam Angle	45°
Working temperature	-20 to + 45 °C
Life span	50,000 h
IP	65
Dimension	W325 x L395 x H225

Technical Features

Materials	Housing-BLACK-Aluminum
Surface Material	Lens-Translucent color-PC
Installation way	Surface
Adjustability	Tilted

Applications

factory, Warehouses, outdoor, Tunnel, Football stadiums, Building lighting, outdoor light applications

Electrical Features

Light source	LM80 SMD Module - SMD
Powered By	HYUNDAI

Scene Application



IES Features

