



## HYD-158R-6W 3K

### Panel light

#### Description

The surface-mounted panel light adopts high-quality LED chips, achieving higher luminous efficacy. It is also equipped with a well-known brand driver to ensure a product lifespan of over 20,000 hours. This luminaire is specifically designed for architectural spaces without suspended ceilings or pre-buried conduits, and can perfectly adapt to various venues.

The HYD - 158R surface-mounted panel light, with its outstanding comprehensive performance, is dedicated to creating a bright, comfortable, healthy, and productivity-enhancing lighting environment for users. It is the ideal lighting choice for modern spaces that pursue quality and efficiency.

#### Product Specification

|                         |                |
|-------------------------|----------------|
| Power                   | 6 W            |
| Luminaire luminous flux | 624 lm         |
| Efficiency              | 104 lm/w       |
| CCT                     | 3000 k         |
| CRI                     | ≥80            |
| Beam Angle              | 115°           |
| Working temperature     | -20 to + 40 °C |
| Life span               | 20,000 h       |
| IP                      | 20             |
| Dimension               | D115 x H33     |

#### Technical Features

|                  |                   |
|------------------|-------------------|
| Materials        | Housing-White-PC  |
| Surface Material | Diffuser-White-PC |
| Installation way | Surface           |
| Adjustability    | Not Adjustable    |

#### Applications

Healthcare, Offices, Schools, Supermarkets, Hospitals & Clinics, Restaurants, Villas, Office, Home

#### Electrical Features

|              |         |
|--------------|---------|
| Light source | HYUNDAI |
| Powered By   | HYUNDAI |

#### Scene Application



#### IES Features

