



Panel light

The surface-mounted panel light adopts high-quality LED chips, achieving higher luminous efficacy. It is also equipped with a well-known brand driver to ensure a product lifespan of over 20,000 hours. This luminaire is specifically designed for architectural spaces without suspended ceilings or pre-buried conduits, and can perfectly adapt to various venues.

Power	18 W
Luminaire luminous flux	2016 lm
Efficiency	112 lm/w
CCT	4000 k
CRI	≥80
Beam Angle	115°
Working temperature	-20 to + 40 °C
Life span	20,000 h
IP	20
Dimension	D224 x H33

Light source	HYUNDAI
Powered By	HYUNDAI

Materials	Housing-White-PC
Surface Material	Diffuser-White-PC
Installation way	Surface
Adjustability	Not Adjustable

Healthcare, Offices, Schools, Supermarkets, Hospitals & Clinics, Restaurants,
Villas, Office, Home

The image displays a radio propagation calculation. On the left is a circular 'MUF' (Maximum Usable Frequency) chart. The chart has concentric circles representing different frequencies and radial lines for bearings. A blue arc is drawn across the chart, centered at 180 degrees, spanning from approximately 114.6 to 114.8 degrees. On the right is a table of data for a radio path, showing frequency, distance, and other parameters. The table has 10 rows of data. Below the table is a small diagram of a radio path with a transmitter and receiver antenna, and a line indicating the path. The diagram is labeled 'AVERAGE BEAN ANGLE (50V) 114.6 DEG'.

Distance	Frequency	Distance	Frequency
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6
100.000	114.6	100.000	114.6

AVERAGE BEAN ANGLE (50V) 114.6 DEG