



HYD-158S-12W 3K

Panel light

Description

The surface-mounted panel light adopts high-quality LED chips, achieving higher luminous efficacy. It is also equipped with a well-known brand driver to ensure a product lifespan of over 20,000 hours. This luminaire is specifically designed for architectural spaces without suspended ceilings or pre-buried conduits, and can perfectly adapt to various venues.

The HYD - 158S surface-mounted panel light, with its outstanding comprehensive performance, is dedicated to creating a bright, comfortable, healthy, and productivity-enhancing lighting environment for users. It is the ideal lighting choice for modern spaces that pursue quality and efficiency.

Product Specification

Power	12 W
Luminaire luminous flux	1236 lm
Efficiency	103 lm/w
CCT	3000 k
CRI	≥80
Beam Angle	115°
Working temperature	-20 to + 40 °C
Life span	20,000 h
IP	20
Dimension	W172 x L172 x H31

Technical Features

Materials	Housing-White-PC
Surface Material	Diffuser-White-PC
Installation way	Surface
Adjustability	Not Adjustable

Applications

Healthcare, Offices, Schools, Supermarkets, Hospitals & Clinics, Villas, Hotel, Dining room, Home

Electrical Features

Light source	HYUNDAI
Powered By	HYUNDAI

Scene Application



IES Features

