



HYD-116CS-15W 3K

Panel light

Description

The HYD-116C recessed panel light features an aluminum body that offers excellent heat dissipation, effectively reducing light depreciation and extending the lifespan of the fixture. This light is equipped with carefully selected LED chips and a highly transparent diffuser, which not only ensures high efficiency and energy savings but also minimizes dark spots in the light distribution. The light is soft and non-glaring, meeting customers' demands for a comfortable and healthy visual environment. Additionally, the HYD-116C recessed panel light adopts an embedded design, seamlessly integrating with various interior styles without being obtrusive and enhancing the aesthetic appeal of the space.

Product Specification

Power	15 W
Luminaire luminous flux	1770 lm
Efficiency	118 lm/w
CCT	3000 k
CRI	≥80
Beam Angle	110°
Working temperature	-10 to + 45 °C
Life span	50,000 h
IP	20
Dimension	W170 x L170 x H27.5
Cut Out	145 x 145 mm

Technical Features

Materials	Housing-White-Aluminum
Surface Material	Diffuser-White-PC
Installation way	Recessed
Adjustability	Not Adjustable

Applications

Healthcare, Offices, Schools, Supermarkets, Restaurants, Hotel

Electrical Features

Light source	HYUNDAI
Powered By	HYUNDAI

Scene Application



IES Features

