



HF22Y-P30-14W 3.5K Ra90

Magnetic track light

Description

Magnetic track lights utilize magnetic attraction to enable the lamp modules to be installed, moved and replaced on electrified tracks without tools. Its 48V DC low-voltage power supply technology allows the lamps to light up immediately upon placement, completing both fixation and power connection. The system includes a variety of light source modules that can be flexibly combined to adapt to lighting solutions such as the no-main-light design. From home living rooms to commercial exhibition halls, from minimalist residences to light luxury offices, the 48V magnetic track lights, with their safety, flexibility and efficiency, truly serve people's needs and change as required.

Product Specification

Power	14 W
Voltage	DC 48V
Luminaire luminous flux	840 lm
Efficiency	60 lm/w
CCT	3500 k
CRI	≥90
Beam Angle	100°
Working temperature	-20 to + 40 °C
Life span	30,000 h
IP	20
Dimension	W23 x L300 x H25

Technical Features

Materials	Housing-Black-Aluminum
Surface Material	Diffuser cover-White-PC
Installation way	On rail
Adjustability	Not Adjustable

Applications

Showrooms, Villas, Museums, Hotel, Dining room, Living room, Home

Electrical Features

Light source	HYUNDAI
Powered By	HYUNDAI

Scene Application



IES Features

